Overview of transducers with Ethernet interface for temperature

Transmitter with Ethernet interface for temperature, humidity, pressure and CO2

[Transducer type H0530](#)



Sensor: Temperatursensor

Temperature range: -30 bis +80°C

Accuracy: ±0,4°C

Protection class electronics: IP40

Power supply: 9 - 30 VDC

Comm.protocol: WWW, Modbus TCP, SNMPv1, SOAP

Special feature:

3 Binäreingänge und 2 Relaisausgänge

(50V, 2A, 60VA)

Large display

[Transducer type H4531](#)



Sensor: Externer Pt1000 Sensor

Temperaturbereich: -200 bis +600°C

Accuracy: ±0,2°C

Protection class electronics: IP40

Power supply: 9-30 VDC

Comm.protocol: WWW, Modbus TCP, SNMPv1, SOAP

Special feature:

3 Binäreingänge und 2 Relaisausgänge

(50V, 2A, 60VA)

Large display

[Transducer type H4531R](#)



Sensor: Externer Pt1000 Sensor

Temperaturbereich: -200 bis +600°C

Accuracy: ±0,2°C

Protection class electronics: IP30

Power supply: 12 VDC

Comm.protocol: WWW, Modbus TCP, SNMPv1, SOAP

Special feature:

3 Binäreingänge und 2 Relaisausgänge

(50V, 2A, 60VA)

Rack Version

Large display

[General Catalog Web-Sensors](#)

[Transducer type P8510](#)



Sensor: Temperatursensor

Temperature range: -30 bis +80°C

Accuracy: ±0,8°C

Protection class electronics: IP30

Power supply: 5 VDC

Comm.protocol: WWW, Modbus TCP, SNMPv1, SOAP

[General Catalog Web-Sensors](#)

[Transducer type P8511](#)



Sensor: Externer Sensor

Temperature range: Sens. abhängig

Accuracy: Sens. abhängig

Protection class electronics: IP30

Power supply: 5 VDC

Comm.protocol: WWW, Modbus TCP, SNMPv1, SOAP, XML

[General Catalog Web-Sensors](#)

[Transducer type P8541](#)



Sensor: Externe Sensoren

Temperature range: Sens. abhängig

Accuracy: Sens. abhängig

Protection class electronics: IP30

Power supply: 5 VDC

Comm.protocol: WWW, Modbus TCP, SNMPv1, SOAP, XML

[General Catalog Web-Sensors](#)

[Transducer type P8610](#)

[General Catalog Web-Sensors](#)

[Transducer type P8611](#)

[General Catalog Web-Sensors](#)

[Transducer type P8641](#)



Sensor: Temperatursensor

Temperature range: -20 bis +60°C

Accuracy: ±0,8°C

Protection class electronics: IP30

Power supply: Power Over Ethernet oder 5 Vdc

Comm.protocol: E-Mail, Modbus TCP, SNMPv1, SOAP, XML

Special feature:

Power over Ethernet

[General Catalog Web-Sensors]

[Transducer type T0510]



Sensor: Externer Sensor

Temperature range: Sens. abhängig

Accuracy: Sens. abhängig

Protection class electronics: IP30

Power supply: Power Over Ethernet oder 5 Vdc

Comm.protocol: WWW, Modbus TCP, SNMPv1, SOAP, XML

Special feature:

Power over Ethernet

1 Channel

[General Catalog Web-Sensors]

[Transducer type T0610]



Sensor: Externe Sensoren

Temperature range: Sens. abhängig

Accuracy: Sens. abhängig

Protection class electronics: IP30

Power supply: Power Over Ethernet oder 5 Vdc

Comm.protocol: WWW, Modbus TCP, SNMPv1, SOAP, XML

Special feature:

Power over Ethernet

4 Channels

[General Catalog Web-Sensors]

[Transducer type T4511]



Sensor: Temperatursensor

Temperature range: -30 bis +80°C

Accuracy: ±0,6°C

Protection class electronics: IP30

Power supply: 9 - 30 Vdc

Comm.protocol: WWW, Modbus TCP, SNMPv1, SOAP, XML

Special feature:

Large display

[General Catalog Web-Sensors]

[Transducer type T4611]





Sensor: Temperatursensor

Temperature range: -20 bis +60°C

Accuracy: ±0,6°C

Protection class electronics: IP30

Power supply: Power Over Ethernet oder 5 Vdc

Comm.protocol: WWW, Modbus TCP, SNMPv1, SOAP, XML

Special feature:

Power over Ethernet

Large display

[General Catalog Web-Sensors]



Sensor: ext. Pt1000 Sensor

Temperature range: -200 bis +600°C

Accuracy: ±0,2°C

Protection class electronics: IP30

Power supply: 9 - 30 Vdc


Comm.protocol: WWW, Modbus TCP, SNMPv1, SOAP, XML

Special feature:

Large display

[General Catalog Web-Sensors]

[Cover / weather station]



Sensor: ext. Pt1000 Sensor

Temperature range: -200 bis +600°C

Accuracy: ±0,2°C

Protection class electronics: IP30

Power supply: PoE oder 5 Vdc

Comm.protocol: WWW, Modbus TCP, SNMPv1, SOAP, XML

Special feature:

Power over Ethernet (PoE)

Large display

Protective cover for weather sensors

- Universally applicable
- Robust
- Inexpansive

General Catalog Web-Sensors

Schutzabdeckung für Wettersensoren

Opening the Download-Files May require the Adobe-Acrobat-Reader.
Click here to download the Adobe-Acrobat-Reader.

If you have questions please don't hesitate to contact us any time.

Phone +49 (89) 3133007, **Fax** +49 (89) 3146706, wuntronic@wuntronic.de or send us our Contact form

Wuntronic GmbH, Heppstrasse 30, D-80995 Munich, Germany